

**Draft Amendment for Patent Application Serial No. 09/865,108****IN THE CLAIMS:**

Claims 2, 3, 5, 9, and 14 are amended herein. All pending claims are produced below. In addition, the status of each is also indicated below.

1. (Previously Presented) An electronic device, comprising:  
a radio unit configured to communicate with a network;  
at least one memory device configured to store application and system programs; and  
a processing unit coupled to said radio unit and said at least one memory device, said  
processing unit configured to run the application and system programs;  
wherein at least one of the application and system programs include a software  
enabled switch displayed on the device screen for enabling and disabling  
the radio unit while leaving the processing unit in an operation state.
2. (Currently Amended) An electronic device comprising:  
a radio unit configured to communicate with a network;  
at least one memory device configured to store application and system programs; and  
a processing unit couples to said radio unit and said at least one memory device, said  
processing unit configured to run the application and system programs;  
wherein:  
at least one of the application and system programs ~~include~~ includes a software  
enabled switch for enabling and disabling the radio unit;  
at least one of said application and system programs is a program that utilizes the  
radio unit; and  
at least one of said application and system programs comprises a notification program  
configured to notify a user ~~if that~~ the radio unit is disabled ~~upon~~ when  
invoking a program that is configured to utilize ~~utilizes~~ the radio unit.

**Draft Amendment for Patent Application Serial No. 09/865,108**

3. (Currently Amended) The electronic device according to Claim 2, wherein said notification program is further configured to give the user an option to either, continue executing the ~~application or system~~ program that is configured to utilize the radio unit and automatically enable the radio unit device, or

discontinue execution of the ~~application or system~~ program that is configured to utilize the radio unit and leaving the radio unit disabled.

4. (Original) The electronic device according to Claim 1, wherein: said device further comprises a display screen; and at least one of said system and application programs are configured to generate a graphical user interface on the display screen having at least one soft button programmed to enable and disable said radio device.

5. (Currently Amended) The electronic device according to Claim 4, wherein said graphical user interface is a GUI having a first soft button entitled "**RADIO ON**," and a second soft button labeled "~~Radio~~ **RADIO OFF**," and an enablement status of the radio device is indicated by the corresponding soft button highlighted in one of bold, inverse video, flashing, or other indicators.

6. (Original) The electronic device according to Claim 1, further comprising a hard button programmed to enable and disable the radio device, wherein said hard button is a toggle switch that is activated by engaging the hard button for a predetermined length of time.

7. (Original) The electronic device according to Claim 6, wherein said hard button has at least one additional program invoked by pressing the hard button for a time period less than said predetermined length of time.

**Draft Amendment for Patent Application Serial No. 09/865,108**

8. (Original) The electronic device according to Claim 6, wherein said predetermined length of time is approximately 1 second.

9. (Currently Amended) The electronic device according to Claim 1, wherein:  
said software enabled switch includes;  
a user interface with a drop down menu having user selectable options for Radio On,  
Radio Off, and Schedule, and  
programming configured to implement an option selected by the user.

10. (Original) The electronic device according to Claim 1, wherein the application and system programs include a scheduling application that provides user modifiable start and stop times that indicate when the radio unit is enabled and disabled.

11. (Previously Presented) A notification mechanism for notifying a user of a status of an RF device in an RF capable device, wherein the RF capable device includes a processing unit for running applications and a user interface, said notification mechanism comprising:

a check mechanism configured to check an enablement status of the RF device;  
a user interface mechanism configured to display a status of the RF device and a  
software enabled switch on a touch-sensitive screen, providing the user  
with an option to continue with the program requiring RF capabilities and  
automatically enable the RF device or discontinue the program requiring  
RF capabilities without enabling the RF device; and  
an RF alarm mechanism configured to identify a program that is previously invoked  
that requires the RF capabilities of the RF capable device, wherein upon  
identifying the program, the RF alarm mechanism wakes the notification  
mechanism from a "sleep" mode and the notification mechanism checks

**Draft Amendment for Patent Application Serial No. 09/865,108**

the enablement status of the RF device using said check mechanism, and if the RF device is not enabled, the notifications mechanism invokes the user interface mechanism.

12. (Original) A method of notifying a user of an RF enablement status of a device having RF capabilities, comprising the steps of:

identifying the invocation of a mechanism requiring access to the RF capabilities;

determining the RF enablement status of the RF device;

if the RF device is not enabled:

prompting a user of the device if the mechanism is to be granted RF access, and

retrieving a user input regarding whether RF access should be granted to the

mechanism requiring RF access;

if the user input indicates the mechanism is to be granted RF access: automatically

enabling the RF device, and

allowing the mechanism requiring RF access to continue and access the RF device;

and

if the user input indicates the mechanism should not be granted RF access, then,

shutting down the mechanism requiring RF access without enabling the

RF device.

13. (Previously Presented) An electronic device, comprising:

a radio unit;

at least one of an application and system program configured to access the radio unit;

a processing unit coupled to said radio unit and said at least one memory device, said

processing unit configured to run the at least one application and system program;

**Draft Amendment for Patent Application Serial No. 09/865,108**

a software enabled switch displayed on the device screen for enabling and disabling the radio unit while leaving the processing unit in an operational state; and said at least one application and system program includes a prompting mechanism configured to display a prompt to a user to determine if the radio unit is to be enabled before enabling the radio unit.

14. (Currently Amended) The electronic device according to Claim 13, wherein: said at least one application and system program includes a notification mechanism to identify when the radio unit ~~is has been~~ enabled.

15. (Previously Presented) The electronic device according to Claim 14, wherein the notification mechanism comprises display of an airplane icon.

16. (Previously Presented) The electronic device according to Claim 13, further comprising a shutdown device configured to maintain the radio unit in a non enabled state, maintain the processing unit in an operational state, and shut down an application program that utilizes the radio unit upon a negative response to the prompt from the user.

17. (Previously presented) The electronic device according to Claim 1, further comprising a status display indicating enablement of the radio unit, wherein the status display comprises an airplane icon.

18. (Previously Presented) The electronic device according to Claim 2, further comprising a status display indicating enablement of the radio unit, wherein the status display comprises an airplane icon.

**Draft Amendment for Patent Application Serial No. 09/865,108**

19. (Previously Presented) The notification mechanism according to Claim 11, further comprising a display indicating enablement status of the radio unit, wherein the display comprises an airplane icon.

20. (Previously Presented) The method according to Claim 12, further comprising the step of displaying the enablement status of the RF device using an icon that comprises an airplane.